


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₂	REVISED	PATLAN 9-09-98	<i>[Signature]</i> 4/19/99
B	PER EC 0U20-0116-01-03	13NOV01	<i>C. Hoang</i> 13NOV01

HOUSING COUPLING NUT SLIDE ASS'Y	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	ELECTRO-POLISHED
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
CONTACT EXT.	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CENTER CONTACT	BRASS PER ASTM-B-16, HALF HARD	GOLD PLATE PER MIL-G-45204
COMPONENT	MATERIAL	FINISH

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY	DATE	 AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY		
FRAC. ± 1/64	DEC. ± .020	ANGLES ± 1°	
These drawings and speci- fications are the property of AMP Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	APP'D BY	DATE	TITLE 7mm PRECISION TO "OSP" PLUG ADAPTER
	USE ASSY PROCEDURE		
NO. A.P. N/A	SIZE	CODE IDENT NO.	REV
	B	26805	4581-2700-00 01 ₂
	SCALE	4:1	SHEET 1 OF 1

NOTES:
 1. CAPTURED CENTER CONTACT
 2. SPECIFICATION;
 FREQ. RANGE: DC TO 18.0 GHz
 MAX VSWR 1.03 + .004f(GHz)

.XXX = in
 XX.X = mm (REF)