

170-03135



Article Number: 170-03135

Description: Braided Sleeving, Split Wrap, .75" Dia, PET, Black, 500 ft/bulk reel

Base Data	Local Order Number	170-03135
	Type	BSPSW340LB
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Split wrap design installs quickly, saving assembly time and future accessibility without disassembly. • Unique construction retains shape and rigidity throughout unrolling. • Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.
	Quantity Per	reel
	Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
	Short Description	Braided Sleeving, Split Wrap, .75" Dia, PET, Black, 500 ft/bulk reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		152.4m
Reel Length (imperial)		500.0ft
Bundle Diameter Max. (Imperial)		0.75"
Bundle Diameter Max. (Metric)		19.1mm
Nominal Diameter (Imperial)		3/4"
Nominal Diameter (Metric)		19.1mm
Material and Specifications		Material
	Material Shortcut	PET
	Flammability	UL 94 V0
	Operating Temperature	-94°F to +248°F (-70°C to +125°C)

170-03135



Material and Specifications	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500ft
	Package Quantity (Metric)	152.4m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	16.8lbs
	Weight (Metric)	7.6kg