

170-03061

Article Number: 170-03061



Description: Braided Sleeving, Resin Coated Fiberglass, 1" Dia, GF, Black, 25 ft/reel

Base Data	Local Order Number	170-03061
	Type	BSHTFG100
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• An extremely tough sleeving material which provides thermal protection up to 1,200°F.</li> <li>• Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.</li> <li>• Cuts easily with ordinary scissors for easy application.</li> <li>• UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.</li> </ul>
	Quantity Per	reel
	Product Description	An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.
	Short Description	Braided Sleeving, Resin Coated Fiberglass, 1" Dia, GF, Black, 25 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		7.62m
Reel Length (imperial)		25.0ft
Bundle Diameter Max. (Imperial)		1.625"
Bundle Diameter Max. (Metric)		41.3mm
Diameter D (imperial)		1.0"
Nominal Diameter (Imperial)		1"
Nominal Diameter (Metric)		25.4mm
Material and Specifications	Material	Glass Fiber (GF)
	Material Shortcut	GF
	Flammability	VW-1

170-03061



Material and Specifications	Operating Temperature	-94°F to +1202°F (-70°C to +650°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25ft
	Package Quantity (Metric)	7.62m
	Customs Number(Schedule B)	7019901000
	Weight (imperial)	2.61lbs
	Weight (Metric)	1.2kg