



PANDUIT PART NUMBER	WEIGHT
FITF6X4	0.70 LB/EACH (317g/EACH)



NOTES:

1. SEE CURRENT CATALOG FOR ADDITIONAL PART SUFFIXES TO INDICATE PACKAGE QUANTITY.
2. THE FIBERRUNNER 6x4 INNERDUCT TRANSITION FITTING ATTACHES TO ANY FIBERRUNNER 6x4 CHANNEL AND/OR FITTING AS WELL AS THE FIBERRUNNER 12x4 VERTICAL TEE FITTING TO CREATE A FLEXIBLE SPILL-OUT INTO EQUIPMENT FRAMES AND TELECOMMUNICATIONS CABINETS. THE INNERDUCT TRANSITION IS DESIGNED TO SECURELY HOLD UP TO FOUR (4) PIECES OF 1 1/2" (38.1) I.D. INNERDUCT AND/OR SOLID CORRUGATED LOOM TUBING.
3. THE FIBERRUNNER 6x4 INNERDUCT TRANSITION FITTING INCLUDES:
ONE (1) INNERDUCT TRANSITION FITTING,
THREE (3) #10-32x1/2 PAN HEAD PHILLIPS MACHINE SCREWS,
THREE (3) #10 HELICAL SPRINGS LOCKWASHERS,
THREE (3) #10-32 HEX MACHINE SCREW NUTS,
TWO (2) BT41 - DOME-TOP BARB-TY CABLE TIES
4. FINISH COLOR: BLACK (EXCEPT HARDWARE)
5. DIMENSIONS IN PARENTHESES ARE IN METRIC.

ENG. REF.: D37585DD_DC_FITF6X4_04.prt

CAD FILENAME/LAYERS: FITF6X4.pdf

PANDUIT CORP. TINLEY PARK, ILLINOIS
FIBERRUNNER 6x4 INNERDUCT TRANSITION FITTING (FITF6X4)
 CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:
 (.X) ± (.XXX) ±
 (.XX) ± .03 (.8) ANGLES ±

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY: JHNU
 DATE: 10-3-00
 CHECK'D: CVV

MAT'L: STEEL

SCALE: NONE

DRAWING NO.: 37585-76
 DWG SIZE: A

REV	DATE	BY	CHK	DESCRIPTION	ECN	R	CUST	SUP	GMBH
-	-----	---	---	I. REVISED PART WEIGHT	-----	--	--		
-	-----	---	---	H. REVISED GENERAL NOTES G. REVISED CAD FILENAME	-----	--	--		
2	6-23-06	DTP	RN	F. REVISED DRAWING TITLE E. REVISED AND REDRAWN	37585-76	RN	RN		