

HC-A 4-ESTS

Order No.: 1774911



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1774911>

HEAVYCON male insert, A4 series, 4-pos., screw connection without wire protection

Commercial data

EAN	4017918122249
Pack	10 pcs.
Customs tariff	85366990
Weight/Piece	0.01848 KG
Catalog page information	Page 423 (PC-2009)

Product notes

WEEE/RoHS-compliant since:
01/31/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Note	For housing HC-D7
Connection method	Screw connection
Tightening torque	0.25 Nm
Ambient temperature (operation)	-40 °C ... 125 °C (including heating up of contacts)
Pollution degree	3

Surge voltage category	III
Constructional and testing regulations	DIN VDE 0627/86
	DIN VDE 0110/02.79
	DIN VDE 0110-1/04.97
	IEC 60664-1, DIN IEC 60512
	IEC 60352
Number of positions	4
Insertion/withdrawal cycles	≥ 500
Design	A4
Connection in acc. with standard	IEC / EN
Conductor cross section	0.5 mm ² ... 1.5 mm ²
Connection cross section AWG	20 ... 16
Stripping length of the individual wire	5 mm
Assembly instructions	Connectors may be operated only when there is no load/voltage.

Material data

Inflammability class acc. to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA

Electrical characteristics

Rated voltage (III/3)	230 V (Conductor-PE)
	400 V (Conductor-Conductor)
Rated surge voltage	4 kV
Rated current	10 A

Certificates / Approvals



Certification CSA, GOST, UL


CSA

Nominal voltage U _N	600 V
Nominal current I _N	10 A

Diagrams/Drawings


Diagram

Derating diagram: Series HC-A 3-E..S / HC-A 4-E..S




Dimensioned drawing

Male insert



Schematic diagram

Connector pin assignment connection side: Left pin; right socket



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;