

DESCRIPTION: 35° ENTRY - DIE CAST





DIMENSIONS (IN.)					
No. OF PINS	Α	В	С	D	E
09	1.693	0.610	0.984	1.260	0.512
15	1.693	0.610	1.312	1.591	0.512
25	1.890	0.610	1.852	2.126	0.512
37	2.087	0.610	2.500	2.776	0.512

SPECIFICATION:

MATERIAL: ZINC, NICKEL PLATED,

COPPER UNDER PLATE

BACKSHELL KIT INCLUDES:

(2) BACKSHELL HALVES

(2) STRAIN RELIEF CLAMPS

(2) STRAIN RELIEF SCREWS

(2) MOUNTING SCREWS

(2) THUMBSCREWS ***(SEE NOTE)***

(3-SETS) METALIZED PLASTIC INSERTS


NOTE:

9-POSITION - 1 LONG THUMBSCREW WITH PLASTIC CAP 15-POSITION - 1 LONG THUMBSCREW WITH PLASTIC CAP 1 SHORT THUMBSCREW WITH METAL CAP

25-POSITION - 1 LONG THUMBSCREW WITH PLASTIC CAP

1 SHORT THUMBSCREW WITH PLASTIC CAP 37-POSITION - 1 LONG THUMBSCREW WITH PLASTIC CAP

1 SHORT THUMBSCREW WITH PLASTIC CAP



DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: DATE: C. SMITH CHECKED: DATE:

NorComp

SCALE: SHEET REV 1 1:1 DWG NO. 953-YYY-030R121

03-26-07

RoHS COMPLIANT