

8 Port Gigabit Industrial Ethernet Switch

EIR408-T



PRODUCT FEATURES

- 8 10/100/1000 Base-T Ethernet ports
- UL Class 1/Division 2
- NEMA TS2
- Dual 12 to 48 VDC power inputs
- Wide operating temperature (-40 to 75°C)

The EIR408-T is an 8 Port Unmanaged Industrial Gigabit Ethernet Switch. Packed full of rugged features, this switch is perfect for your high speed industrial network.

High-Speed Transmissions: The EIR408-T includes a switch controller that automatically senses transmission speed (10/100/1000 Mbps). The RJ-45 interface also auto-detects MDI or MDI-X, eliminating the requirement for a crossover cable. Each port is buffered and supports store-and-forward protocol.

Dual Power Input: To reduce the risk of power failure, the EIR408-T provides two 12 to 48 VDC power inputs. If the power fails, the switch will automatically use the secondary power input. Also, if the power goes out the corresponding P1 or P2 LED will go out and the Fault LED will light. The contacts for the alarm output will also open.

Flexible Mounting: The switch features a space saving IP30 metal enclosure that can be DIN or Panel mounted.

Wide Operating Temperature: With an operating temperature of -40 to 75°C (-40 to 167°F), this switch can be used in harsh industrial environments.

Easy Troubleshooting: There are two LED indicators for each port that display the link status and transmission speed. Three LED indicators for power (P1, P2 and Fault) show power status. These indicators allow you to quickly diagnose and correct problems and ensure your network remains reliable.

ORDERING INFORMATION

| MODEL NUMBER | DESCRIPTION |
|--------------|----------------------------------|
| EIR408-T | 8 Port Industrial Gigabit Switch |

ACCESSORIES

C5UMB7FBG - Category 5e, 7 ft. (2.1 M), Grey

EIRSP1 - Industrial Ethernet Surge Suppressor

MDR-20-24 - DIN rail mount power supply 24VDC, 1.0 A output power

MDR-40-24 - DIN rail mount power supply 24VDC, 1.7 A output power

MDR-60-24 - DIN rail mount power supply 24VDC, 2.5 A output power

8 Port Gigabit Industrial Ethernet Switch

EIR408-T



SPECIFICATIONS

| IEEE STANDARDS | |
|------------------------|--|
| IEEE 802.3 | 802.3. 10Base-T Ethernet |
| IEEE 802.3u | 100Base-TX and 100Base-FX Fast Ethernet |
| IEEE 802.3ab | 1000Base-T |
| IEEE 802.3x | Flow Control and Back Pressure |
| NETWORK SPECIFICATIONS | |
| Architecture | Back-plane (Switching Fabric): 10Gbps Throughput (Full-dup): 14.88Mpps@64bytes |
| Transmission Speed | Up to 1000 Mbps |
| Buffer | 136 Kbits |
| MAC Table | 8K |
| Jumbo Frame | 9.6Kbytes |
| Other | Broadcast Storm Protection |
| INTERFACE | |
| RJ-45 Ports | 8 x 10/100/1000BaseT, Auto MDI/MDI-X |
| LED Indicators | P1 (Power 1), P2 (Power 2), Fault (Power Fault), RJ-45 Ports have 2 LED's to indicate LINK and activity |
| POWER | |
| Input Voltage | Dual 12 to 48 VDC Inputs Reverse Polarity Protection |
| Power Connection | Removable Terminal Block |
| Wire Size | 12 to 24 AWG |
| Power Use | 7.788 Watts |
| Fault Output | 1 Relay Output – Normally Closed |
| EFT Protection | 3000 V EFT Protection |

| ENVIRONMENTAL | |
|-----------------------|--|
| Operating Temperature | - 40 to 75°C (-40 to 167°F) |
| Storage Temperature | - 40 to 85°C (-40 to 185°F) |
| Operating Humidity | 0 to 95% |
| MECHANICAL | |
| Enclosure | IP30 Metal Enclosure |
| Mounting | 35mm DIN Rail or Panel Mount Attachments |
| Dimensions | 3.0 x 14.0 x 9.5 cm (1.18 x 5.51 x 3.74 in) |
| CERTIFICATIONS | |
| Safety | CE EN60950-1 |
| Hazardous Location | UL/cUL Class I, Division 2, Groups A, B, C and D |
| EMC | FCC Class A, CE EN61000-4-2 (ESD) CE EN61000-4-3 (RS) CE EN61000-4-4 (EFT) CE EN61000-4-5 (Surge) CE EN61000-4-6 (CS) CE EN61000-4-8 CE EN61000-6-2 CE EN61000-6-4 |
| Free Fall | IEC60068-2-32 |
| Shock | IEC60068-2-27 |
| Vibration | IEC60068-2-6 |
| NEMA TS2 | |

MECHANICAL DIAGRAM

