

170-03051



Article Number: 170-03051

Description: Braided Sleeving, Resin Coated Fiberglass, .5" Dia, GF, Black, 200 ft/bulk reel

Base Data	Local Order Number	170-03051
	Type	BSHTFG120B
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• An extremely tough sleeving material which provides thermal protection up to 1,200°F.</li> <li>• Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.</li> <li>• Cuts easily with ordinary scissors for easy application.</li> <li>• UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.</li> </ul>
	Quantity Per	reel
	Product Description	An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.
	Short Description	Braided Sleeving, Resin Coated Fiberglass, .5" Dia, GF, Black, 200 ft/bulk reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		61.0m
Reel Length (imperial)		200.0ft
Bundle Diameter Max. (Imperial)		0.75"
Bundle Diameter Max. (Metric)		19.1mm
Nominal Diameter (Imperial)		1/2"
Nominal Diameter (Metric)		12.7mm
Material and Specifications		Material
	Material Shortcut	GF
	Flammability	VW-1
	Operating Temperature	-94°F to +1202°F (-70°C to +650°C)

170-03051



Material and Specifications	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	200ft
	Package Quantity (Metric)	60.96m
	Customs Number(Schedule B)	7019901000
	Weight (imperial)	9.6lbs
	Weight (Metric)	4.35kg