

115-01200

Article Number: 115-01200

Description: Releasable Cable Tie, Release Tab, 8.9" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg



Base Data	
Local Order Number	RT255S0HIRX2
Type	RT255S
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> <li>• High impact, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.</li> <li>• Special design offers a release feature for quick and easy access to wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li> </ul>
Quantity Per	bag
Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force . For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Releasable Cable Tie, Release Tab, 8.9" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	250.0lbs
Minimum Tensile Strength (Metric)	1115.0N
Length L (Imperial)	8.9"
Length L (Metric)	225.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	Yes
Width W (Imperial)	0.5"
Width W (Metric)	12.6mm
Bundle Diameter Min. (Imperial)	0.49"
Bundle Diameter Min. (Metric)	12.5mm
Bundle Diameter Max. (Imperial)	2.2"
Bundle Diameter Max. (Metric)	55.0mm

115-01200



Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
	Certification/Specification	UL
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3926909987