

170-03072

Article Number: 170-03072



Description: Braided Sleeveing, Expandable, Flame Retardant, .25" Dia, PET, Gray, 200 ft/reel

Base Data	Local Order Number	170-03072
	Type	BSPFR148
	Color	Gray (GY)
	Features and Benefits	<ul style="list-style-type: none"> • Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required. • Braided design allows sleeveing to expand by 150% to accommodate variations in wire bundle and eases installation.
	Quantity Per	reel
	Product Description	A flame retardant woven (threaded) polyester sleeveing that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.
	Short Description	Braided Sleeveing, Expandable, Flame Retardant, .25" Dia, PET, Gray, 200 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		61.0m
Reel Length (imperial)		200.0ft
Bundle Diameter Min. (Imperial)		0.125"
Bundle Diameter Min. (Metric)		3.2mm
Bundle Diameter Max. (Imperial)		0.437"
Bundle Diameter Max. (Metric)		11.1mm
Nominal Diameter (Imperial)		1/4"
Nominal Diameter (Metric)		6.4mm
Material and Specifications		Material
	Material Shortcut	PET
	Flammability	FMVSS 302

170-03072



Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	200ft
	Package Quantity (Metric)	60.96m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.48lbs
	Weight (Metric)	0.22kg